

- TPA-CF

DESCRIPTION

One component solvent-based ink with glossy finish for pad printing.

SUBSTRATES

ABS, PC

FEATURES

- Excellent printability
- Quick drying
- Good adhesion
- Good light fastness
- Good mechanical resistances

TPA-CF serie is in compliance with:

- EN 71-3: 2013+A1:2014
- ISO 8124-3: 2010+Amd 1:2014
- Applicable Parts ANNEX XVII of REACH including Phthalates

TECHNICAL DATA

PAD PRINTING	
Cliché	From 26 to 40 micron
Pad	5-15 shore
Drying	<ul style="list-style-type: none"> • Dust free after some minutes at room temperature, completely dried after 24 hours • Some minutes with hot air
Thinners	<i>Thinner TPA (VXTHTPAL1)</i> <i>Thinner Tagless Fast (VXTHTSOL1)</i> <i>Retarder 4 (VXTH4L1)/(VXTH4L5)</i>
Cleaning	Ethyl Acetate, Acetone

PREPARATION

Before using, the ink must be well mixed and, in case, diluted according to the printing requirements.

COLOUR RANGE**WHITES AND BLACKS**

Codice	Prodotto	Pack.
VX9900.E001K1	TPA-CF White EO	1 Kg
VX9900.E002K1	TPA-CF Black EO	1 Kg
VX9900.E0LK1	TPA-CF WHITE L	1 Kg
VX9900.E0MK1	TPA-CF BLACK M	1 Kg

COLOURS

Codice	Prodotto	Pack.
VX9900.E0AK1	TPA-CF LEMON YELLOW A	1 Kg
VX9900.E0ABK1	TPA-CF MEDIUM YELLOW AB	1 Kg
VX9900.E0BK1	TPA-CF GOLDEN YELLOW B	1 Kg
VX9900.E0CK1	TPA-CF ORANGE C	1 Kg
VX9900.E0DK1	TPA-CF RED D	1 Kg
VX9900.E0EK1	TPA-CF CARMINE E	1 Kg
VX9900.E0FK1	TPA-CF PINK F	1 Kg
VX9900.E0GK1	TPA-CF BRIGHT VIOLET G	1 Kg
VX9900.E0HK1	TPA-CF PERMANENT BLUE H	1 Kg
VX9900.E0KK1	TPA-CF PERMANENT GREEN K	1 Kg

OTHER PRODUCTS

Codice	Prodotto	Pack.
VX99GLDK1	PAD CF Glow in the Dark	1 Kg

TRANSPARENT

Codice	Prodotto	Pack.
VX9900.E49K1	TPA-CF CLEAR	1 Kg

STORAGE

The products, kept in their sealed original packages, have a shelf-life of one year.

IMPORTANT NOTE

The information given in this technical sheet is not intended to be exhaustive and any person, using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us of the suitability of the product for the intended purpose, does so at his own risk.

While we endeavour to ensure that all advice we give about the product is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product.

Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage arising out of the use of the product.

The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.